

Validity: 60 days

#### Minimum Technical Requirements for CTG MACHINE

## > PRODUCT SPECIFICATIONS

- Performance specification
  - o Ultrasound
    - Technique
      - Ultrasound pulse Doppler with autocorrelation
    - Pulse repetition rate
      - 2KHz
    - Pulse duration
      - 92μs
    - Ultrasound frequency
      - 1.0 ± 10% MHz
    - Ultrasound signal range
      - 3.5μV Vpp 350 μV Vpp
      - Max output power
        - <15mW
    - FHR measurement range
      - 50 240 bpm
      - Resolution : 1 bpm
      - Accuracy : ± 1bpm
  - o DECG
    - Technique
      - Peak peak detection technique
    - DFHR measurement range
      - 30 240 bpm
    - Resolution
      - 1 bpm
      - Accuracy

PREPARED & REVIEWED BY

END USER: \_\_\_\_\_\_ DESIGNATION: \_\_\_\_\_\_

JAMES CARLTY D. LABADAN, ECE CHAIRPERSON

KEVIN S. CATAGUE, ECE JOEL L. LUNA VICE-CHAIRPERSON MEMBER

**IVAN PAUL L. TANO, ECE** MEMBER

CE CRIS ABEL M. GUEVARRA, MPA MEMBER

APPROVED BY:

RICHARD B. SISON, MD, MHA, FPCHA, FPSMS Medical Center Chief II Page | 1



Validity: 60 days

#### Minimum Technical Requirements for CTG MACHINE

±1 bpm TOCO 0 Toco range 0-100% • Page | 2 Non linear error ±10% • Resolution 1% Fetal movement Technique 0 Pulsed Doppler ultrasound Fm mode 0 Automatic or manual AFM mode 0 Trace or blackmark Display range 0 0 – 999 ➢ ECG HR measurement range 0 30 – 240 bpm HR measuring accuracy 0 ±2 bpm ECG waveform 0 Manual control ECG waveform display Sweep speed 0 25 mm/s Sensitivity 2.5 mm/mV PREPARED & REVIEWED BY END USER: DESIGNATION: JAMES CARLTY D. LABADAN, ECE **KEVIN S. CATAGUE, ECE** JOEL L. LUNA IVAN PAUL L. TANO, ECE CRIS ABEL M. GUEVARRA, MPA CHAIRPERSON VICE-CHAIRPERSON MEMBER MEMBER MEMBER APPROVED BY: RICHARD B. SISON, MD, MHA, FPCHA, FPSMS Medical Center Chief II

Philhealth Accredited REVISION: 7



Validity: 60 days

#### Minimum Technical Requirements for CTG MACHINE

- 5mm/mV
- 10mm/mV
- 20mm/mV
- AUTO gain
- > SpO2

0

- Measurement range
  - 50 100 %
  - Resolution
    - 1%
- Measurement accuracy
  - 90 100% : ±2%
  - 70 90 %: ±4%
- PR measurement range
  - 30 240 bpm
  - Accuracy: ± 3 bpm
- Physical specification
  - o Dimesion
    - Not larger than 350 x 350 x 150 DWH
  - Weight
    - Not heavier than 6.5 kgs
  - Power supply

- 220 240 Vac
- Battery
  - 14.8Vdc/ at least 5000 mAh
- Ingress protection
  - Main unit
    - At least IPX1

PREPARED & REVIEWED BY

END USER: \_\_\_\_\_\_ DESIGNATION: \_\_\_\_\_\_

JAMES CARLTY D. LABADAN, ECE CHAIRPERSON KEVIN S. CATAGUE, ECEJOEL L. LUNAVICE-CHAIRPERSONMEMBER

**IVAN PAUL L. TANO, ECE** MEMBER

CRIS ABEL M. GUEVARRA, MPA MEMBER

APPROVED BY:

RICHARD B. SISON, MD, MHA, FPCHA, FPSMS Medical Center Chief II

> Philhealth Accredited REVISION: 7

Page | 3



Validity: 60 days

# Minimum Technical Requirements for CTG MACHINE

- US & TOCO transducers
  - At least IPX8
- o Display
  - LCD size
    - Not smaller than 12 inches
    - Pixel : 800H x 600V

#### Standard compliance

- ISO 81060-2:2013: Non-invasive sphygmomanometer
- o IEC/EN 60601-2-27: Electrocardiographic monitoring equipment
- IEC/EN 60601-2-37: Basic safety and essential performance of ultrasonic diagnostic equipment

## STANDARD ACCESSORIES:

## NOTE: accessories sets is per unit

- Ultrasound gel 1 bottle
- 10 packs thermal paper
- Automatic voltage regulator
- > Trolley

## STANDARD REQUIREMENTS UPON SUBMISSION OF BIDDING DOCUMENTS

# Soft copy of user manual REQUIREMENT/S IF AWARDED THE CONTRACT

# Unit must be BRAND NEW.

Manual in English Language

PREPARED & REVIEWED BY

END USER:	
DESIGNATION:	

JAMES CARLTY D. LABADAN, ECE CHAIRPERSON KEVIN S. CATAGUE, ECE JOE VICE-CHAIRPERSON MEI

JOEL L. LUNA MEMBER IVAN PAUL L. TANO, ECE MEMBER CRIS ABEL M. GUEVARRA, MPA MEMBER

APPROVED BY:

RICHARD B. SISON, MD, MHA, FPCHA, FPSMS Medical Center Chief II Page | 4



Validity: 60 days

### Minimum Technical Requirements for CTG MACHINE

- 2 copy of Operation manual (Hard copy)
- Service manual with soft copy
- ➤ Training Program
  - for end-user on equipment's operation with certificate
  - Technical training with certificate (When necessary)
- > Three (3) years warranty on parts and service after commissioning and acceptance
- > Certification on the availability of spare parts for the next 5 years
- > Down time of machine will be added as extension of the warranty.
- > With calibration certificate (When necessary)
- Supplier must respond to a service call before 72 hours and should be onsite not more than 7 days.
- > Section V. Special Conditions of the Contract
  - Delivery Place: Margosatubig Regional Hospital, Zamboanga del Sur
- Section VI Schedule of Requirements
  - Completion/Delivery Period: \_\_\_\_\_ calendar days upon receipt of the Notice to Proceed including the delivery, installation, testing and commissioning, Partial delivery allowed within the completion/delivery period.

PREPARED & REVIEWED BY					
END USER: DESIGNATION:					
JAMES CARLTY D. LABADAN, ECE CHAIRPERSON	KEVIN S. CATAGUE, ECE VICE-CHAIRPERSON	<b>JOEL L. LUNA</b> MEMBER	IVAN PAUL L. TANO, ECE MEMBER	<b>CRIS ABEL M. GUEVARRA, MPA</b> MEMBER	
APPROVED BY:					
RICHARD B. SISON, MD, Medical Center Chief II	MHA, FPCHA, FPSMS				

Page | 5

Philhealth Accredited REVISION: 7