

Validity: 60 days

Minimum Technical Requirements for DEFIBRILLATOR MACHINE

PRODUCT SPECIFICATIONS

≻ ECG

- 3, 5 and 10 leads
- o Internal and external reusable paddles
- Loose lead indicator
- o Size
 - 2.5 mm/mV
 - 10 mm/mV
 - 20 mm/mV
 - 40 mm/mV
- On screen speed of ECG
 - 25 mm/sec
- Frequency response
 - MAINS filter
 - 50/60Hz
 - Diagnostic
 - 0.05 150 Hz
 - Muscle filter
 - 0.67 40 Hz
 - On-screen response
 - 0.05 40 Hz
- Heart rate
 - 30 300 bpm
- Heart rate response time
 - From 80 40 bpm : 8 seconds
 - From 80 120 bpm: 5 seconds
 - Alarm response time for tachycardia
 - 206 bpm (1mV): 3 seconds

PREPARED & REVIEWED BY

END USER: ______ DESIGNATION: ______

JAMES CARLTY D. LABADAN, ECE CHAIRPERSON

KEVIN S. CATAGUE, ECEJOEL L. LUNAVICE-CHAIRPERSONMEMBER

IVAN PAUL L. TANO, ECE MEMBER

CRIS ABEL M. GUEVARRA, MPA MEMBER

APPROVED BY:

FM-MCC-005

RICHARD B. SISON, MD, MHA, FPCHA, FPSMS Medical Center Chief II

> Philhealth Accredited REVISION: 7

Page | 1



Validity: 60 days

Minimum Technical Requirements for DEFIBRILLATOR MACHINE

- 195 bpm (2mV): 3 seconds
- Alarms
 - Visual alarm
 - Sound alarm
 - General alarm
 - Unit ready for shock
 - Lead off alarm
- Defibrillator
 - Waveform

- Truncated exponential biphasic
 - Output energy accuracy
 - ±15%
 - Patient impedance range
 - 25 300 ohms
- Manual defibrillator
 - Output enery
 - External paddle
 - 1 360 joules
 - Paddle
 - Reusable external paddles
 - Multifunction disposable electrodes
 - Charge control
 - Front panel button
 - External paddle button
 - Charging time
 - 5seconds at 200 J
 - 7 seconds at 360 J
- Automated defibrillator

PREPARED & REVIEWED BY

END USER: ______ DESIGNATION: ______

JAMES CARLTY D. LABADAN, ECE CHAIRPERSON KEVIN S. CATAGUE, ECEJOEL L. LUNAVICE-CHAIRPERSONMEMBER

IVAN PAUL L. TANO, ECE MEMBER

CRIS ABEL M. GUEVARRA, MPA MEMBER

APPROVED BY:

RICHARD B. SISON, MD, MHA, FPCHA, FPSMS Medical Center Chief II Page | 2

Philhealth Accredited REVISION: 7



Validity: 60 days

Minimum Technical Requirements for DEFIBRILLATOR MACHINE

- Output energy
 - 150 360 Joule ±15%
- o Guiding messages
 - Audible and screen messages that guide the user during operation
 - Charge indication
 - Charging tone
 - Charge complete tone
 - Flashing shock button on the front panel
- Shock control
 - Front panel button
- Detection characteristics
 - VF sensitivity
 - VT sensitivity
 - NSR specificity
- NIBP

0

- Systolic pressure
 - Adult: 50– 250 mmHg
 - Pedia: 50 150 mmHg
- Diastolic pressure
 - Adult: 30 190 mmHg
 - Pedia: 30 100 mmHg
- Screen
 - Not smaller than 170 x 120 mm screen size
 - o TFT color with LED backlight
 - Resolution: at least 800 x 600 pixel
- Data storage
 - Compact flash removable external memory
 - At least 16 MB

PREPARED & REVIEWED BY

END USER: ______

JAMES CARLTY D. LABADAN, ECE CHAIRPERSON KEVIN S. CATAGUE, ECEJOEL L. LUNAVICE-CHAIRPERSONMEMBER

IVAN PAUL L. TANO, ECE MEMBER

CRIS ABEL M. GUEVARRA, MPA MEMBER

APPROVED BY:

FM-MCC-005

RICHARD B. SISON, MD, MHA, FPCHA, FPSMS Medical Center Chief II

> Philhealth Accredited REVISION: 7

Page | 3



Validity: 60 days

Minimum Technical Requirements for DEFIBRILLATOR MACHINE

- Power supply
 - o 220 240 Vac
 - Battery
 - NiMH or better
 - Charging time not more than 3 hours
- Standard compliance
 - IEC 61000 4 2
 - IEC 61000 4 4
 - IEC 61000 4 11

STANDARD ACCESSORIES:

NOTE: accessories sets is per unit

- Reusable electrode 5 packs
- Automatic voltage regulator

STANDARD REQUIREMENTS UPON SUBMISSION OF BIDDING DOCUMENTS

Soft copy of user manual

REQUIREMENT/S IF AWARDED THE CONTRACT

- ➤ Unit must be BRAND NEW.
- Manual in English Language
 - 2 copy of Operation manual (Hard copy)
 - Service manual with soft copy
 - **Training Program**
 - for end-user on equipment's operation with certificate

PREPARED & REVIEWED BY

END USER:
DESIGNATION:

JAMES CARLTY D. LABADAN,	ECE
CHAIRPERSON	

KEVIN S. CATAGUE, ECEJOEL L. LUNAVICE-CHAIRPERSONMEMBER

IVAN PAU MEMBER

IVAN PAUL L. TANO, ECE CRIS ABEL M. GUEVARRA, MPA MEMBER MEMBER

APPROVED BY:

RICHARD B. SISON, MD, MHA, FPCHA, FPSMS Medical Center Chief II

> Philhealth Accredited REVISION: 7



Validity: 60 days

Minimum Technical Requirements for **DEFIBRILLATOR MACHINE**

- Technical training with certificate (When necessary)
- > Three (3) years warranty on parts and service after commissioning and acceptance
- > Certification on the availability of spare parts for the next 5 years
- > Down time of machine will be added as extension of the warranty.
- With calibration certificate (When necessary)
- Supplier must respond to a service call before 72 hours and should be onsite not more than 7 days.
- Section V. Special Conditions of the Contract
 - Delivery Place: Margosatubig Regional Hospital, Zamboanga del Sur
- Section VI Schedule of Requirements
 - Completion/Delivery Period: _____ calendar days upon receipt of the Notice to Proceed including the delivery, installation, testing and commissioning, Partial delivery allowed within the completion/delivery period.

PREPARED & REVIEWED BY END USER: DESIGNATION: JAMES CARLTY D. LABADAN, ECE **KEVIN S. CATAGUE, ECE** JOEL L. LUNA IVAN PAUL L. TANO, ECE CRIS ABEL M. GUEVARRA, MPA CHAIRPERSON VICE-CHAIRPERSON MEMBER MEMBER MEMBER APPROVED BY: RICHARD B. SISON, MD, MHA, FPCHA, FPSMS Medical Center Chief II

Page | 5

Philhealth Accredited REVISION: 7